



T Onyx 120C ep79 HA84



T Onyx 140R ep79 MHA84



T Onyx 2212C epa83 HP88

EPOXY (ep../epa..) - Ø 40x40 mm - HT75 - incl. regelschroef - vis de réglage - Stellschraube - adjusting screw

Onyx HPL / HA / HM / MEL / MHA

		120C	100	110	120	120D	140R	120V	2212C	2412E	189	210	120CD	100CD	159C
L x B		circ. 120x120	Ø100	Ø110	Ø120	Ø120+40x120	Ø140	120x120	Danish oval 220x120	ellipse 240x120	180x90	200x100	circ. 120+40x120	circ. 100+40x100	Danish oval 150x90
H (hpl)	ht75 ht90	76,0	76,0	76,0	76,0	75,8	75,2	75,8	75,8	75,8	75,8	75,8			
BD (mm)	HPL/HA HM MEL/MHA	26 mm - -	26 mm 18 mm -	26 mm - -	26 mm - -	24 mm - -	- - 18 mm	24 mm - -	24 mm - -	24 mm - -	24 mm 18 mm -	24 mm 18 mm -	24 mm - -	24 mm - -	24 mm - -
PH PB PL	HT75	73,4 - -	73,4 - -	73,4 - -	73,4 - -	72,6 - -	73,4 - -	73,4 - -	72,0 - 99,0	73,4 - 99,0	73,4 - 99,0	73,4 - 99,0			
m³ (ht75)		0,19	0,15	0,17	0,19	0,19	0,24	0,19	0,31	0,32	0,21	0,25			
kg (ht75)	HPL/HA HM MEL/MHA	31,8-36,3 - -	23,8-27,4 23,7-27,3 -	26,6-30,5 - -	29,4-33,9 - -	47,3-52,1 - -	- - 29,8-36,1	32,5-37,0 - -	53,9-62,6 - -	53,4-61,2 - -	39,3-44,9 39,2-44,8 -	45,3-51,3 45,2-51,2 -	- - -	- - -	- - -

